



LEICA V-LUX 5

Technical data.



Camera	Leica V-Lux 5
Order no.	19120 (E-Version), 19121 (U-Version), 19122 (TK-Version), 19123 (IN-Version)
Lens	Leica DC Vario-Elmarit f/2.8-4/9.1 -146 ASPH., 35 mm camera equivalent: 25 - 400 mm 15 elements in 11 groups (5 aspherical lenses/8 aspherical surfaces/4 ED lenses).
Optical Image stabilization	Yes
Zoom Optical/digital/ intelligent	16 x/4 x/32 x
Focusing	
Modes	Normal/macro
AF Metering modes	Face, eye detection, tracking, 49-area, 1-area (flexible/scalable), custom multi, pinpoint
Focusing range	
AF	30 cm/1' (at 9.1 mm)/1m/3'3" (at 146 mm) to ∞.
AF macro/MF/ snapshot	3 cm/1 3/16" (at 9.1 mm)/1m/3'3" (at 146 mm) to ∞.
Sensor	1" MOS with 20.9 MP (effective pixels 20.1MP)
Resolution	
Still image	4:3 format: 4864 × 3648 (17.5 M) (L), 3456 × 2592 (9 M) (M), 2432 × 1824 (4.5 M) (S). 3:2 format: 5472 × 3648 (20 M) (L), 3888 × 2592 (10 M) (M), 2736 × 1824 (5 M) (S). 16:9 format: 5472 × 3080 (17 M) (L), 3840 × 2160 (8 M) (M), 1920 × 1080 (2 M) (S). 1:1 format: 3648 × 3648 (13.5 M) (L), 2592 × 2592 (6.5 M) (M), 1824 × 1824 (3.5 M) (S).
Video	MP4: [4K] 3840 x 2160 4K/30p: 100 Mbit/s [4K] 3840 x 2160 4K/24p: 100 Mbit/s [FHD] 1920x1080 FHD/60p: 28 Mbit/s [FHD] 1920x1080 FHD/30p: 20 Mbit/s [HD] 1280 x 720 HD/30p: 10 Mbit/s
Recording file formats	
Still image	RAW/JPEG
Video	MP4. Recording time: max. 29:00 minutes
Audio	AAC (2 Kanal)
Exposure control	
Exposure modes	Snap Shot, P, A, S, M, creative video, C1 (custom), C2 (custom), scene guide, creative control
Exposure compensation	Increments: 1/3 EV steps, setting range: ± 5 EV. (+/-3 EV for motion picture)
Auto AE Bracketing	3, 5, 7 frames in 1/3, 2/3 or 1 EV step, max. ± 3 EV.

Scene modes	Clear portrait, silky skin, backlit softness, clear in backlight, relaxing tone, sweet child's face, distinct scenery, bright blue sky, romantic sunset glow, vivid sunset glow, glistening water, clear nightscape, cool night sky, warm glowing nightscape, artistic aightscape, glittering illuminations, handheld night shot, clear night portrait, soft image of a flower, appetizing food, cute dessert, freeze animal motion, clear sports shot, monochrome, panorama
Creative control modes	Expressive, retro, old days, high key, low key, sepia, monochrome, dynamic monochrome, rough monochrome, silky monochrome, impressive art, high dynamic, cross process, toy effect, toy pop, bleach bypass, miniature effect, soft focus, fantasy, star filter, one point color, sunshine
Metering modes	Intelligent multiple, centre-weighted, spot
White balance	Auto, daylight, cloudy, shade, incandescent, flash, 4 manual settings, color temperature (2-axis adjustable)
ISO sensitivity	Auto/i. ISO/80, 100, 200, 400, 800, 1600, 3200, 6400, 12500, 25000* (*extended ISO) (Changeable to 1/3 EV step)
Shutter speeds	Still image Approx. 60s – 1/4000 s (mechanical shutter), approx. 1 s – 1/16000 s (electronic shutter). Bulb: approx. 120 s. Motion picture Approx. 1/30 s – 1/16000 s (NTSC model), approx. 1/25 s – 1/16000 s (PAL model), approx. 1/2 s – 1/16000 s. (Creative video M mode/MF mode)
Continuous shooting	[AFS] SH: 50 frames/sec*, H: 12 frames/s, M: 7 frames/s (with Live View), L: 2 frames/s (with Live View.) (*Electronic shutter only)
Flash	Integrated flash
Flash modes	Auto, Auto with pre-flash (red-eye reduction), Auto with slow sync and pre-flash, on, off
Flash range	30 cm – 13.5 m (Wide/ISO Auto), 1.0 – 9.5 m (Tele/ISO Auto)
Self-timer	2 s/10s/10 s (3 images)
Monitor	3.0" TFT LCD, resolution: approx. 1,240,000 pixels, Image field: approx. 100%, aspect ratio 3:2, Touch screen available
Viewfinder	0.39" OLED live viewfinder Resolution: approx. 2,360,000 pixels, Image field: approx. 100%, aspect ratio 4:3, Diopter setting: -4 to +4 dptr, Magnification: approx. 0.74x with 50mm lens at ∞; -1.0m-1
Microphone/speaker	Stereo/monoaural
Memory cards	On SD / SDHC* /SDXC* memory cards, *UHS-I/UHS Speed class 3
Interfaces	USB 2.0, Macro-HDMI (Typ C), AV-output, 2.5 mm for remote, 3.5 mm for external microphone. WIFI: IEEE 802.11b/g/n/2412 MHz - 2462 MHz (1-11-Kanal)/WPA/WPA2/Infrastructure mode/WPS/ Wi-Fi Direct/Wi-Fi Taste Bluetooth-Version 4.2 (Bluetooth Low Energy (BLE) [USB/CHARGE] USB 2.0 (High Speed) Mikro-B
Operating temperature/humidity	0 °C to 40 °C (32 °F to 104 °F) / 10% to 80% RH
Rechargeable lithium-ion battery	
Voltage/capacity	7.2 V / 1200 mAh (360 images, CIPA standard).
Dimensions (W x H x D)	approx. 136.7 x 97.2 x 131.5 mm
Weight	812 g (with battery).
Printer compatibility	PictBridge, DPOF
Scope of delivery	Digital camera, battery, AC-Adapter, USB cable, neck strap, lens cap with string, lens hood, hot shoe cover, instructions, guarantee card